


EXPRESS MAIL CERTIFICATE

"EXPRESS MAIL" LABEL NO.: EL978749710US

Date of Deposit: 09/02/03

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above, addressed to: M.S.: Patent Application, Commissioner for Patents, P.O. Box 1450, Alexandria, Va 22313-1450.


Gretchen King

APPLICATION FOR UNITED STATES LETTERS PATENT

FOR

DOWNHOLE CUTTING MILL

Inventors: Sven Krueger
Celle, Germany
Volker Krueger
Celle, Germany
Harald Grimmer
Lachendorf, Germany
Jorg Breitenfeld
Bergen, Germany

Assignee: Baker Hughes Incorporated
3900 Essex Lane, Suite 1920
Houston, Texas 77027

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of U.S. Patent Application No. 10/251,138 filed Sept. 20, 2002, which takes priority from U.S. provisional patent application serial number 60/323,803 filed on September 20, 2001,
5 titled "Active Controlled Bottomhole Pressure System and Method."

Field of the Invention

This invention relates generally to oilfield wellbore drilling systems and more particularly to drilling systems that utilize active control of bottomhole
10 pressure or equivalent circulating density during drilling of the wellbores.

Background of the Art

Oilfield wellbores are drilled by rotating a drill bit conveyed into the wellbore by a drill string. The drill string includes a drill pipe (tubing) that has
15 at its bottom end a drilling assembly (also referred to as the "bottomhole assembly" or "BHA") that carries the drill bit for drilling the wellbore. The drill pipe is made of jointed pipes. Alternatively, coiled tubing may be utilized to carry the drilling of assembly. The drilling assembly usually includes a drilling motor or a "mud motor" that rotates the drill bit. The drilling assembly also
20 includes a variety of sensors for taking measurements of a variety of drilling, formation and BHA parameters. A suitable drilling fluid (commonly referred to as the "mud") is supplied or pumped under pressure from a source at the surface down the tubing. The drilling fluid drives the mud motor and then discharges at the bottom of the drill bit. The drilling fluid returns uphole via
25 the annulus between the drill string and the wellbore inside and carries with it pieces of formation (commonly referred to as the "cuttings") cut or produced by the drill bit in drilling the wellbore.

For drilling wellbores under water (referred to in the industry as
30 "offshore" or "subsea" drilling) tubing is provided at a work station (located on a vessel or platform). One or more tubing injectors or rigs are used to move the tubing into and out of the wellbore. In riser-type drilling, a riser, which is formed by joining sections of casing or pipe, is deployed between the drilling

vessel and the wellhead equipment at the sea bottom and is utilized to guide the tubing to the wellhead. The riser also serves as a conduit for fluid returning from the wellhead to the sea surface.

During drilling, the drilling operator attempts to carefully control the fluid
5 density at the surface so as to control pressure in the wellbore, including the
bottomhole pressure. Typically, the operator maintains the hydrostatic
pressure of the drilling fluid in the wellbore above the formation or pore
pressure to avoid well blow-out. The density of the drilling fluid and the fluid
flow rate largely determine the effectiveness of the drilling fluid to carry the
10 cuttings to the surface. One important downhole parameter controlled during
drilling is the bottomhole pressure, which in turn controls the equivalent
circulating density ("ECD") of the fluid at the wellbore bottom.

This term, ECD, describes the condition that exists when the drilling
15 mud in the well is circulated. The friction pressure caused by the fluid
circulating through the open hole and the casing(s) on its way back to the
surface, causes an increase in the pressure profile along this path that is
different from the pressure profile when the well is in a static condition (i.e.,
not circulating). In addition to the increase in pressure while circulating, there
20 is an additional increase in pressure while drilling due to the introduction of
drill solids into the fluid. This negative effect of the increase in pressure along
the annulus of the well is an increase of the pressure which can fracture the
formation at the shoe of the last casing. This can reduce the amount of hole
that can be drilled before having to set an additional casing. In addition, the
25 rate of circulation that can be achieved is also limited. Also, due to this
circulating pressure increase, the ability to clean the hole is severely
restricted. This condition is exacerbated when drilling an offshore well. In
offshore wells, the difference between the fracture pressures in the shallow
sections of the well and the pore pressures of the deeper sections is
30 considerably smaller compared to on shore wellbores. This is due to the
seawater gradient versus the gradient that would exist if there were soil
overburden for the same depth.

In some drilling applications, it is desired to drill the wellbore at at-balance condition or at under-balanced condition. The term at-balance means that the pressure in the wellbore is maintained at or near the formation pressure. The under-balanced condition means that the wellbore pressure is below the formation pressure. These two conditions are desirable because the drilling fluid under such conditions does not penetrate into the formation, thereby leaving the formation virgin for performing formation evaluation tests and measurements. In order to be able to drill a well to a total wellbore depth at the bottomhole, ECD must be reduced or controlled. In subsea wells, one approach is to use a mud- filled riser to form a subsea fluid circulation system utilizing the tubing, BHA, the annulus between the tubing and the wellbore and the mud filled riser, and then inject gas (or some other low density liquid) in the primary drilling fluid (typically in the annulus adjacent the BHA) to reduce the density of fluid downstream (i.e., in the remainder of the fluid circulation system). This so-called "dual density" approach is often referred to as drilling with compressible fluids.

Another method for changing the density gradient in a deepwater return fluid path has been proposed, but not used in practical application. This approach proposes to use a tank, such as an elastic bag, at the sea floor for receiving return fluid from the wellbore annulus and holding it at the hydrostatic pressure of the water at the sea floor. Independent of the flow in the annulus, a separate return line connected to the sea floor storage tank and a subsea lifting pump delivers the return fluid to the surface. Although this technique (which is referred to as "dual gradient" drilling) would use a single fluid, it would also require a discontinuity in the hydraulic gradient line between the sea floor storage tank and the subsea lifting pump. This requires close monitoring and control of the pressure at the subsea storage tank, subsea hydrostatic water pressure, subsea lifting pump operation and the surface pump delivering drilling fluids under pressure into the tubing for flow downhole. The level of complexity of the required subsea instrumentation and controls as well as the difficulty of deployment of the system has delayed

(if not altogether prevented) the practical application of the "dual gradient" system.

Another approach is described in U.S. Patent Application No. 09/353,275, filed on July 14, 1999 and assigned to the assignee of the present application. The U.S. Patent Application No. 09/353,275 is incorporated herein by reference in its entirety. One embodiment of this application describes a riser less system wherein a centrifugal pump in a separate return line controls the fluid flow to the surface and thus the equivalent circulating density.

The present invention provides a wellbore system wherein the bottomhole pressure and hence the equivalent circulating density is controlled by creating a pressure differential at a selected location in the return fluid path with an active pressure differential device to reduce or control the bottomhole pressure. The present system is relatively easy to incorporate in new and existing systems.

SUMMARY OF THE INVENTION

The present invention provides wellbore systems for performing downhole wellbore operations for both land and offshore wellbores. Such drilling systems include a rig that moves an umbilical (e.g., drill string) into and out of the wellbore. A bottomhole assembly, carrying the drill bit, is attached to the bottom end of the drill string. A well control assembly or equipment on the well receives the bottomhole assembly and the tubing. A drilling fluid system supplies a drilling fluid into the tubing, which discharges at the drill bit and returns to the well control equipment carrying the drill cuttings via the annulus between the drill string and the wellbore. A riser dispersed between the wellhead equipment and the surface guides the drill string and provides a conduit for moving the returning fluid to the surface.

In one embodiment of the present invention, an active pressure differential device moves in the wellbore as the drill string is moved. In an

alternative embodiment, the active differential pressure device is attached to the wellbore inside or wall and remains stationary relative to the wellbore during drilling. The device is operated during drilling, *i.e.*, when the drilling fluid is circulating through the wellbore, to create a pressure differential across the device. This pressure differential alters the pressure on the wellbore below or downhole of the device. The device may be controlled to reduce the bottomhole pressure by a certain amount, to maintain the bottomhole pressure at a certain value, or within a certain range. By severing or restricting the flow through the device, the bottomhole pressure may be increased.

The system also includes downhole devices for performing a variety of functions. Exemplary downhole devices include devices that control the drilling flow rate and flow paths. For example, the system can include one or more flow-control devices that can stop the flow of the fluid in the drill string and/or the annulus. Such flow-control devices can be configured to direct fluid in drill string into the annulus and/or bypass return fluid around the APD device. Another exemplary downhole device can be configured for processing the cuttings (*e.g.*, reduction of cutting size) and other debris flowing in the annulus. For example, a comminution device can be disposed in the annulus upstream of the APD device.

In a preferred embodiment, sensors communicate with a controller via a telemetry system to maintain the wellbore pressure at a zone of interest at a selected pressure or range of pressures. The sensors are strategically positioned throughout the system to provide information or data relating to one or more selected parameters of interest such as drilling parameters, drilling assembly or BHA parameters, and formation or formation evaluation parameters. The controller for suitable for drilling operations preferably includes programs for maintaining the wellbore pressure at zone at under-balance condition, at at-balance condition or at over-balanced condition. The controller may be programmed to activate downhole devices according to programmed instructions or upon the occurrence of a particular condition.

Exemplary configurations for the APD Device and associated drive includes a moineau-type pump coupled to positive displacement motor/drive via a shaft assembly. Another exemplary configuration includes a turbine drive coupled to a centrifugal-type pump via a shaft assembly. Preferably, a high-pressure seal separates a supply fluid flowing through the motor from a return fluid flowing through the pump. In a preferred embodiment, the seal is configured to bear either or both of radial and axial (thrust) forces.

In still other configurations, a positive displacement motor can drive an intermediate device such as a hydraulic motor, which drives the APD Device. Alternatively, a jet pump can be used, which can eliminate the need for a drive/motor. Moreover, pumps incorporating one or more pistons, such as hammer pumps, may also be suitable for certain applications. In still other configurations, the APD Device can be driven by an electric motor. The electric motor can be positioned external to a drill string or formed integral with a drill string. In a preferred arrangement, varying the speed of the electrical motor directly controls the speed of the rotor in the APD device, and thus the pressure differential across the APD Device.

20

Bypass devices are provided to allow fluid circulation in the wellbore during tripping of the system, to control the operating set points of the APD Device and/or associated drive/motor, and to provide a discharge mechanism to relieve fluid pressure. For examples, the bypass devices can selectively channel fluid around the motor/drive and the APD Device and selectively discharge drilling fluid from the drill string into the annulus. In one arrangement, the bypass device for the pump can also function as a particle bypass line for the APD device. Alternatively, a separate particle bypass can be used in addition to the pump bypass for such a function. Additionally, an annular seal (not shown) in certain embodiments can be disposed around the APD device to enable a pressure differential across the APD Device.

Examples of the more important features of the invention have been summarized (albeit rather broadly) in order that the detailed description thereof that follows may be better understood and in order that the contributions they represent to the art may be appreciated. There are, of course, additional features of the invention that will be described hereinafter and which will form the subject of the claims appended hereto.

BRIEF DESCRIPTION OF THE DRAWINGS

For detailed understanding of the present invention, reference should be made to the following detailed description of the preferred embodiment, taken in conjunction with the accompanying drawing:

Figure 1A is a schematic illustration of one embodiment of a system using an active pressure differential device to manage pressure in a predetermined wellbore location;

Figure 1B graphically illustrates the effect of an operating active pressure differential device upon the pressure at a predetermined wellbore location;

Figure 2 is a schematic elevation view of **Figure 1A** after the drill string and the active pressure differential device have moved a certain distance in the earth formation from the location shown in **Figure 1A**;

Figure 3 is a schematic elevation view of an alternative embodiment of the wellbore system wherein the active pressure differential device is attached to the wellbore inside;

Figures 4A-D are schematic illustrations of one embodiment of an arrangement according to the present invention wherein a positive displacement motor is coupled to a positive displacement pump (the APD Device);

Figures 5A and 5B are schematic illustrations of one embodiment of an arrangement according to the present invention wherein a turbine drive is coupled to a centrifugal pump (the APD Device);

Figure 6A is a schematic illustration of an embodiment of an arrangement according to the present invention wherein an electric motor disposed on the outside of a drill string is coupled to an APD Device;

Figure 6B is a schematic illustration of an embodiment of an arrangement according to the present invention wherein an electric motor disposed within a drill string is coupled to an APD Device;

Figure 7 schematically illustrates one embodiment of a comminution device made in accordance with the teachings of the present invention;

Figure 8 schematically illustrates an exemplary non rotating chamber part for the **Fig. 7** embodiment;

Figure 9 schematically illustrates an exemplary cutting head for the **Fig. 7** embodiment;

Figure 10 schematically illustrates another exemplary cutting head for the **Fig. 7** embodiment; and

Figure 11 schematically illustrated another embodiment of a comminution device made in accordance with the teachings of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Referring initially to **Figure 1A**, there is schematically illustrated a system for performing one or more operations related to the construction, logging, completion or work-over of a hydrocarbon producing well. In particular, **Figure 1A** shows a schematic elevation view of one embodiment of a wellbore drilling system **100** for drilling wellbore **90** using conventional drilling fluid circulation. The drilling system **100** is a rig for land wells and includes a drilling platform **101**, which may be a drill ship or another suitable surface workstation such as a floating platform or a semi-submersible for offshore wells. For offshore operations, additional known equipment such as a riser and subsea wellhead will typically be used. To drill a wellbore **90**, well control equipment **125** (also referred to as the wellhead equipment) is placed

above the wellbore **90**. The wellhead equipment **125** includes a blow-out-preventer stack **126** and a lubricator (not shown) with its associated flow control.

5 This system **100** further includes a well tool such as a drilling assembly or a bottomhole assembly ("BHA") **135** at the bottom of a suitable umbilical such as drill string or tubing **121** (such terms will be used interchangeably). In a preferred embodiment, the BHA **135** includes a drill bit **130** adapted to disintegrate rock and earth. The bit can be rotated by a surface rotary drive
10 or a motor using pressurized fluid (e.g., mud motor) or an electrically driven motor. The tubing **121** can be formed partially or fully of drill pipe, metal or composite coiled tubing, liner, casing or other known members. Additionally, the tubing **121** can include data and power transmission carriers such fluid conduits, fiber optics, and metal conductors. Conventionally, the tubing **121**
15 is placed at the drilling platform **101**. To drill the wellbore **90**, the BHA **135** is conveyed from the drilling platform **101** to the wellhead equipment **125** and then inserted into the wellbore **90**. The tubing **121** is moved into and out of the wellbore **90** by a suitable tubing injection system.

20 During drilling, a drilling fluid from a surface mud system **22** is pumped under pressure down the tubing **121** (a "supply fluid"). The mud system **22** includes a mud pit or supply source **26** and one or more pumps **28**. In one embodiment, the supply fluid operates a mud motor in the BHA **135**, which in turn rotates the drill bit **130**. The drill string **121** rotation can also be used to
25 rotate the drill bit **130**, either in conjunction with or separately from the mud motor. The drill bit **130** disintegrates the formation (rock) into cuttings **147**. The drilling fluid leaving the drill bit travels uphole through the annulus **194** between the drill string **121** and the wellbore wall or inside **196**, carrying the drill cuttings **147** therewith (a "return fluid"). The return fluid discharges into a
30 separator (not shown) that separates the cuttings **147** and other solids from the return fluid and discharges the clean fluid back into the mud pit **26**. As shown in **Figur 1A**, the clean mud is pumped through the tubing **121** while

the mud with cuttings **147** returns to the surface via the annulus **194** up to the wellhead equipment **125**.

Once the well **90** has been drilled to a certain depth, casing **129** with a casing shoe **151** at the bottom is installed. The drilling is then continued to drill the well to a desired depth that will include one or more production sections, such as section **155**. The section below the casing shoe **151** may not be cased until it is desired to complete the well, which leaves the bottom section of the well as an open hole, as shown by numeral **156**.

As noted above, the present invention provides a drilling system for controlling bottomhole pressure at a zone of interest designated by the numeral **155** and thereby the ECD effect on the wellbore. In one embodiment of the present invention, to manage or control the pressure at the zone **155**, an active pressure differential device ("APD Device") **170** is fluidically coupled to return fluid downstream of the zone of interest **155**. The active pressure differential device is a device that is capable of creating a pressure differential " ΔP " across the device. This controlled pressure drop reduces the pressure upstream of the APD Device **170** and particularly in zone **155**.

The system **100** also includes downhole devices that separately or cooperatively perform one or more functions such as controlling the flow rate of the drilling fluid and controlling the flow paths of the drilling fluid. For example, the system **100** can include one or more flow-control devices that can stop the flow of the fluid in the drill string and/or the annulus **194**. **Figure 1A** shows an exemplary flow-control device **173** that includes a device **174** that can block the fluid flow within the drill string **121** and a device **175** that blocks can block fluid flow through the annulus **194**. The device **173** can be activated when a particular condition occurs to insulate the well above and below the flow-control device **173**. For example, the flow-control device **173** may be activated to block fluid flow communication when drilling fluid circulation is stopped so as to isolate the sections above and below the

device **173**, thereby maintaining the wellbore below the device **173** at or substantially at the pressure condition prior to the stopping of the fluid circulation.

5 The flow-control devices **174**, **175** can also be configured to selectively control the flow path of the drilling fluid. For example, the flow-control device **174** in the drill pipe **121** can be configured to direct some or all of the fluid in drill string **121** into the annulus **194**. Moreover, one or both of the flow-control devices **174**, **175** can be configured to bypass some or all of the return fluid
10 around the APD device **170**. Such an arrangement may be useful, for instance, to assist in lifting cuttings to the surface. The flow-control device **173** may include check-valves, packers and any other suitable device. Such devices may automatically activate upon the occurrence of a particular event or condition.

15 The system **100** also includes downhole devices for processing the cuttings (e.g., reduction of cutting size) and other debris flowing in the annulus **194**. For example, a comminution device **176** can be disposed in the annulus **194** upstream of the APD device **170** to reduce the size of entrained
20 cutting and other debris. The comminution device **176** can use known members such as blades, teeth, or rollers to crush, pulverize or otherwise disintegrate cuttings and debris entrained in the fluid flowing in the annulus **194**. The comminution device **176** can be operated by an electric motor, a hydraulic motor, by rotation of drill string or other suitable means. The
25 comminution device **176** can also be integrated into the APD device **170**. For instance, if a multi-stage turbine is used as the APD device **170**, then the stages adjacent the inlet to the turbine can be replaced with blades adapted to cut or shear particles before they pass through the blades of the remaining turbine stages.

30 Sensors **S_{1-n}** are strategically positioned throughout the system **100** to provide information or data relating to one or more selected parameters of

interest (pressure, flow rate, temperature). In a preferred embodiment, the downhole devices and sensors **S_{1-n}** communicate with a controller **180** via a telemetry system (not shown). Using data provided by the sensors **S_{1-n}**, the controller **180** maintains the wellbore pressure at zone **155** at a selected pressure or range of pressures. The controller **180** maintains the selected pressure by controlling the APD device **170** (e.g., adjusting amount of energy added to the return fluid line) and/or the downhole devices (e.g., adjusting flow rate through a restriction such as a valve).

When configured for drilling operations, the sensors **S_{1-n}** provide measurements relating to a variety of drilling parameters, such as fluid pressure, fluid flow rate, rotational speed of pumps and like devices, temperature, weight-on bit, rate of penetration, etc., drilling assembly or BHA parameters, such as vibration, stick slip, RPM, inclination, direction, BHA location, etc. and formation or formation evaluation parameters commonly referred to as measurement-while-drilling parameters such as resistivity, acoustic, nuclear, NMR, etc. One preferred type of sensor is a pressure sensor for measuring pressure at one or more locations. Referring still to **Fig. 1A**, pressure sensor **P₁** provides pressure data in the BHA, sensor **P₂** provides pressure data in the annulus, pressure sensor **P₃** in the supply fluid, and pressure sensor **P₄** provides pressure data at the surface. Other pressure sensors may be used to provide pressure data at any other desired place in the system **100**. Additionally, the system **100** includes fluid flow sensors such as sensor **V** that provides measurement of fluid flow at one or more places in the system.

Further, the status and condition of equipment as well as parameters relating to ambient conditions (e.g., pressure and other parameters listed above) in the system **100** can be monitored by sensors positioned throughout the system **100**: exemplary locations including at the surface (**S1**), at the APD device **170** (**S2**), at the wellhead equipment **125** (**S3**), in the supply fluid (**S4**), along the tubing **121** (**S5**), at the well tool **135** (**S6**), in the return fluid

upstream of the APD device **170 (S7)**, and in the return fluid downstream of the APD device **170 (S8)**. It should be understood that other locations may also be used for the sensors **S_{1-n}**.

5 The controller **180** for suitable for drilling operations preferably includes programs for maintaining the wellbore pressure at zone **155** at under-balance condition, at at-balance condition or at over-balanced condition. The controller **180** includes one or more processors that process signals from the various sensors in the drilling assembly and also controls their operation. The
10 data provided by these sensors **S_{1-n}** and control signals transmitted by the controller **180** to control downhole devices such as devices **173-176** are communicated by a suitable two-way telemetry system (not shown). A separate processor may be used for each sensor or device. Each sensor may also have additional circuitry for its unique operations. The controller
15 **180**, which may be either downhole or at the surface, is used herein in the generic sense for simplicity and ease of understanding and not as a limitation because the use and operation of such controllers is known in the art. The controller **180** preferably contains one or more microprocessors or micro-controllers for processing signals and data and for performing control
20 functions, solid state memory units for storing programmed instructions, models (which may be interactive models) and data, and other necessary control circuits. The microprocessors control the operations of the various sensors, provide communication among the downhole sensors and provide two-way data and signal communication between the drilling assembly **30**,
25 downhole devices such as devices **173-175** and the surface equipment via the two-way telemetry. In other embodiments, the controller **180** can be a hydro-mechanical device that incorporates known mechanisms (valves, biased members, linkages cooperating to actuate tools under, for example, preset conditions).

30

For convenience, a single controller **180** is shown. It should be understood, however, that a plurality of controllers **180** can also be used. For

example, a downhole controller can be used to collect, process and transmit data to a surface controller, which further processes the data and transmits appropriate control signals downhole. Other variations for dividing data processing tasks and generating control signals can also be used.

5

In general, however, during operation, the controller **180** receives the information regarding a parameter of interest and adjusts one or more downhole devices and/or APD device **170** to provide the desired pressure or range or pressure in the vicinity of the zone of interest **155**. For example, the controller **180** can receive pressure information from one or more of the sensors (**S₁-S_n**) in the system **100**. The controller **180** may control the APD Device **170** in response to one or more of: pressure, fluid flow, a formation characteristic, a wellbore characteristic and a fluid characteristic, a surface measured parameter or a parameter measured in the drill string. The controller **180** determines the ECD and adjusts the energy input to the APD device **170** to maintain the ECD at a desired or predetermined value or within a desired or predetermined range. The wellbore system **100** thus provides a closed loop system for controlling the ECD in response to one or more parameters of interest during drilling of a wellbore. This system is relatively simple and efficient and can be incorporated into new or existing drilling systems and readily adapted to support other well construction, completion, and work-over activities.

In the embodiment shown in **Figure 1A**, the APD Device **170** is shown as a turbine attached to the drill string **121** that operates within the annulus **194**. Other embodiments, described in further detail below can include centrifugal pumps, positive displacement pump, jet pumps and other like devices. During drilling, the APD Device **170** moves in the wellbore **90** along with the drill string **121**. The return fluid can flow through the APD Device **170** whether or not the turbine is operating. However, the APD Device **170**, when operated creates a differential pressure thereacross.

As described above, the system **100** in one embodiment includes a controller **180** that includes a memory and peripherals **184** for controlling the operation of the APD Device **170**, the devices **173-176**, and/or the bottomhole assembly **135**. In **Figure 1A**, the controller **180** is shown placed at the surface. It, however, may be located adjacent the APD Device **170**, in the BHA **135** or at any other suitable location. The controller **180** controls the APD Device to create a desired amount of ΔP across the device, which alters the bottomhole pressure accordingly. Alternatively, the controller **180** may be programmed to activate the flow-control device **173** (or other downhole devices) according to programmed instructions or upon the occurrence of a particular condition. Thus, the controller **180** can control the APD Device in response to sensor data regarding a parameter of interest, according to programmed instructions provided to said APD Device, or in response to instructions provided to said APD Device from a remote location. The controller **180** can, thus, operate autonomously or interactively.

During drilling, the controller **180** controls the operation of the APD Device to create a certain pressure differential across the device so as to alter the pressure on the formation or the bottomhole pressure. The controller **180** may be programmed to maintain the wellbore pressure at a value or range of values that provide an under-balance condition, an at-balance condition or an over-balanced condition. In one embodiment, the differential pressure may be altered by altering the speed of the APD Device. For instance, the bottomhole pressure may be maintained at a preselected value or within a selected range relative to a parameter of interest such as the formation pressure. The controller **180** may receive signals from one or more sensors in the system **100** and in response thereto control the operation of the APD Device to create the desired pressure differential. The controller **180** may contain pre-programmed instructions and autonomously control the APD Device or respond to signals received from another device that may be remotely located from the APD Device.

Figure 1B graphically illustrates the ECD control provided by the above-described embodiment of the present invention and references **Figure 1A** for convenience. **Figure 1A** shows the APD device **170** at a depth **D1** and a representative location in the wellbore in the vicinity of the well tool **30** at a lower depth **D2**. **Figure 1B** provides a depth versus pressure graph having a first curve **C1** representative of a pressure gradient before operation of the system **100** and a second curve **C2** representative of a pressure gradients during operation of the system **100**. Curve **C3** represents a theoretical curve wherein the ECD condition is not present; *i.e.*, when the well is static and not circulating and is free of drill cuttings. It will be seen that a target or selected pressure at depth **D2** under curve **C3** cannot be met with curve **C1**. Advantageously, the system **100** reduces the hydrostatic pressure at depth **D1** and thus shifts the pressure gradient as shown by curve **C3**, which can provide the desired predetermined pressure at depth **D2**. In most instances, this shift is roughly the pressure drop provided by the APD device **170**.

Figure 2 shows the drill string after it has moved the distance "d" shown by $t_1 - t_2$. Since the APD Device **170** is attached to the drill string **121**, the APD Device **170** also is shown moved by the distance d.

As noted earlier and shown in **Figure 2**, an APD Device **170a** may be attached to the wellbore in a manner that will allow the drill string **121** to move while the APD Device **170a** remains at a fixed location. **Figure 3** shows an embodiment wherein the APD Device is attached to the wellbore inside and is operated by a suitable device **172a**. Thus, the APD device can be attached to a location stationary relative to said drill string such as a casing, a liner, the wellbore annulus, a riser, or other suitable wellbore equipment. The APD Device **170a** is preferably installed so that it is in a cased upper section **129**. The device **170a** is controlled in the manner described with respect to the device **170** (**Fig 1A**).

Referring now to **Figures 4A-D**, there is schematically illustrated one arrangement wherein a positive displacement motor/drive **200** is coupled to a moineau-type pump **220** via a shaft assembly **240**. The motor **200** is connected to an upper string section **260** through which drilling fluid is pumped from a surface location. The pump **220** is connected to a lower drill string section **262** on which the bottomhole assembly (not shown) is attached at an end thereof. The motor **200** includes a rotor **202** and a stator **204**. Similarly, the pump **220** includes a rotor **222** and a stator **224**. The design of moineau-type pumps and motors are known to one skilled in the art and will not be discussed in further detail.

The shaft assembly **240** transmits the power generated by the motor **200** to the pump **220**. One preferred shaft assembly **240** includes a motor flex shaft **242** connected to the motor rotor **202**, a pump flex shaft **244** connected to the pump rotor **224**, and a coupling shaft **246** for joining the first and second shafts **242** and **244**. In one arrangement, a high-pressure seal **248** is disposed about the coupling shaft **246**. As is known, the rotors for moineau-type motors/pump are subject to eccentric motion during rotation. Accordingly, the coupling shaft **246** is preferably articulated or formed sufficiently flexible to absorb this eccentric motion. Alternately or in combination, the shafts **242**, **244** can be configured to flex to accommodate eccentric motion. Radial and axial forces can be borne by bearings **250** positioned along the shaft assembly **240**. In a preferred embodiment, the seal **248** is configured to bear either or both of radial and axial (thrust) forces. In certain arrangements, a speed or torque converter **252** can be used to convert speed/torque of the motor **200** to a second speed/torque for the pump **220**. By speed/torque converter it is meant known devices such as variable or fixed ratio mechanical gearboxes, hydrostatic torque converters, and a hydrodynamic converters. It should be understood that any number of arrangements and devices can be used to transfer power, speed, or torque from the motor **200** to the pump **220**. For example, the shaft assembly **240** can utilize a single shaft instead of multiple shafts.

As described earlier, a comminution device can be used to process entrained cutting in the return fluid before it enters the pump **200**. Such a comminution device (**Figure 1A**) can be coupled to the drive **200** or pump **220** and operated thereby. For instance, one such comminution device or cutting mill **270** can include a shaft **272** coupled to the pump rotor **224**. The shaft **272** can include a conical head or hammer element **274** mounted thereon. During rotation, the eccentric motion of the pump rotor **224** will cause a corresponding radial motion of the shaft head **274**. This radial motion can be used to resize the cuttings between the rotor and a comminution device housing **276**.

The **Figures 4A-D** arrangement also includes a supply flow path **290** to carry supply fluid from the device **200** to the lower drill string section **262** and a return flow path **292** to channel return fluid from the casing interior or annulus into and out of the pump **220**. The high pressure seal **248** is interposed between the flow paths **290** and **292** to prevent fluid leaks, particularly from the high pressure fluid in the supply flow path **290** into the return flow path **292**. The seal **248** can be a high-pressure seal, a hydrodynamic seal or other suitable seal and formed of rubber, an elastomer, metal or composite.

Additionally, bypass devices are provided to allow fluid circulation during tripping of the downhole devices of the system **100** (**Fig. 1A**), to control the operating set points of the motor **200** and pump **220**, and to provide safety pressure relief along either or both of the supply flow path **290** and the return flow path **292**. Exemplary bypass devices include a circulation bypass **300**, motor bypass **310**, and a pump bypass **320**.

The circulation bypass **300** selectively diverts supply fluid into the annulus **194** (**Fig. 1A**) or casing **C** interior. The circulation bypass **300** is interposed generally between the upper drill string section **260** and the motor

200. One preferred circulation bypass **300** includes a biased valve member **302** that opens when the flow-rate drops below a predetermined value. When the valve **302** is open, the supply fluid flows along a channel **304** and exits at ports **306**. More generally, the circulation bypass can be configured to
5 actuate upon receiving an actuating signal and/or detecting a predetermined value or range of values relating to a parameter of interest (e.g., flow rate or pressure of supply fluid or operating parameter of the bottomhole assembly). The circulation bypass **300** can be used to facilitate drilling operations and to selective increase the pressure/flow rate of the return fluid.

10

The motor bypass **310** selectively channels conveys fluid around the motor **200**. The motor bypass **310** includes a valve **312** and a passage **314** formed through the motor rotor **202**. A joint **316** connecting the motor rotor **202** to the first shaft **242** includes suitable passages (not shown) that allow
15 the supply fluid to exit the rotor passage **314** and enter the supply flow path **290**. Likewise, a pump bypass **320** selectively conveys fluid around the pump **220**. The pump bypass includes a valve and a passage formed through the pump rotor **222** or housing. The pump bypass **320** can also be configured to function as a particle bypass line for the APD device. For
20 example, the pump bypass can be adapted with known elements such as screens or filters to selectively convey cuttings or particles entrained in the return fluid that are greater than a predetermined size around the APD device. Alternatively, a separate particle bypass can be used in addition to the pump bypass for such a function. Alternately, a valve (not shown) in a
25 pump housing **225** can divert fluid to a conduit parallel to the pump **220**. Such a valve can be configured to open when the flow rate drops below a predetermined value. Further, the bypass device can be a design internal leakage in the pump. That is, the operating point of the pump **220** can be controlled by providing a preset or variable amount of fluid leakage in the
30 pump **220**. Additionally, pressure valves can be positioned in the pump **220** to discharge fluid in the event an overpressure condition or other predetermined condition is detected.

Additionally, an annular seal **299** in certain embodiments can be disposed around the APD device to direct the return fluid to flow into the pump **220** (or more generally, the APD device) and to allow a pressure differential across the pump **220**. The seal **299** can be a solid or pliant ring member, an expandable packer type element that expands/contracts upon receiving a command signal, or other member that substantially prevents the return fluid from flowing between the pump **220** (or more generally, the APD device) and the casing or wellbore wall. In certain applications, the clearance between the APD device and adjacent wall (either casing or wellbore) may be sufficiently small as to not require an annular seal.

During operation, the motor **200** and pump **220** are positioned in a well bore location such as in a casing **C**. Drilling fluid (the supply fluid) flowing through the upper drill string section **260** enters the motor **200** and causes the rotor **202** to rotate. This rotation is transferred to the pump rotor **222** by the shaft assembly **240**. As is known, the respective lobe profiles, size and configuration of the motor **200** and the pump **220** can be varied to provide a selected speed or torque curve at given flow-rates. Upon exiting the motor **200**, the supply fluid flows through the supply flow path **290** to the lower drill string section **262**, and ultimately the bottomhole assembly (not shown). The return fluid flows up through the wellbore annulus (not shown) and casing **C** and enters the cutting mill **270** via an inlet **293** for the return flow path **292**. The flow goes through the cutting mill **270** and enters the pump **220**. In this embodiment, the controller **180** (**Fig. 1A**) can be programmed to control the speed of the motor **200** and thus the operation of the pump **220** (the APD Device in this instance).

It should be understood that the above-described arrangement is merely one exemplary use of positive displacement motors and pumps. For example, while the positive displacement motor and pump are shown in structurally in series in **Figures 4A-D**, a suitable arrangement can also have a

positive displacement motor and pump in parallel. For example, the motor can be concentrically disposed in a pump.

Referring now to **Figures 5A-B**, there is schematically illustrated one arrangement wherein a turbine drive **350** is coupled to a centrifugal-type pump **370** via a shaft assembly **390**. The turbine **350** includes stationary and rotating blades **354** and radial bearings **402**. The centrifugal-type pump **370** includes a housing **372** and multiple impeller stages **374**. The design of turbines and centrifugal pumps are known to one skilled in the art and will not be discussed in further detail.

The shaft assembly **390** transmits the power generated by the turbine **350** to the centrifugal pump **370**. One preferred shaft assembly **350** includes a turbine shaft **392** connected to the turbine blade assembly **354**, a pump shaft **394** connected to the pump impeller stages **374**, and a coupling **396** for joining the turbine and pump shafts **392** and **394**.

The **Figure 5A-B** arrangement also includes a supply flow path **410** for channeling supply fluid shown by arrows designated **416** and a return flow path **418** to channel return fluid shown by arrows designated **424**. The supply flow path **410** includes an inlet **412** directing supply fluid into the turbine **350** and an axial passage **413** that conveys the supply fluid exiting the turbine **350** to an outlet **414**. The return flow path **418** includes an inlet **420** that directs return fluid into the centrifugal pump **370** and an outlet **422** that channels the return fluid into the casing **C** interior or wellbore annulus. A high pressure seal **400** is interposed between the flow paths **410** and **418** to reduce fluid leaks, particularly from the high pressure fluid in the supply flow path **410** into the return flow path **418**. A small leakage rate is desired to cool and lubricate the axial and radial bearings. Additionally, a bypass **426** can be provided to divert supply fluid from the turbine **350**. Moreover, radial and axial forces can be borne by bearing assemblies **402** positioned along the shaft assembly **390**. Preferably a comminution device **373** is provided to reduce particle size

entering the centrifugal pump **370**. In a preferred embodiment, one of the impeller stages is modified with shearing blades or elements that shear entrained particles to reduce their size. In certain arrangements, a speed or torque converter **406** can be used to convert a first speed/torque of the motor **350** to a second speed/torque for the centrifugal pump **370**. It should be understood that any number of arrangements and devices can be used to transfer power, speed, or torque from the turbine **350** to the pump **370**. For example, the shaft assembly **390** can utilize a single shaft instead of multiple shafts.

10

It should be appreciated that a positive displacement pump need not be matched with only a positive displacement motor, or a centrifugal pump with only a turbine. In certain applications, operational speed or space considerations may lend itself to an arrangement wherein a positive displacement drive can effectively energize a centrifugal pump or a turbine drive energize a positive displacement pump. It should also be appreciated that the present invention is not limited to the above-described arrangements. For example, a positive displacement motor can drive an intermediate device such as an electric motor or hydraulic motor provided with an encapsulated clean hydraulic reservoir. In such an arrangement, the hydraulic motor (or produced electric power) drives the pump. These arrangements can eliminate the leak paths between the high-pressure supply fluid and the return fluid and therefore eliminates the need for high-pressure seals. Alternatively, a jet pump can be used. In an exemplary arrangement, the supply fluid is divided into two streams. The first stream is directed to the BHA. The second stream is accelerated by a nozzle and discharged with high velocity into the annulus, thereby effecting a reduction in annular pressure. Pumps incorporating one or more pistons, such as hammer pumps, may also be suitable for certain applications.

20
25
30

Referring now to **Figure 6A**, there is schematically illustrated one arrangement wherein an electrically driven pump assembly **500** includes a motor **510** that is at least partially positioned external to a drill string **502**. In a

conventional manner, the motor **510** is coupled to a pump **520** via a shaft assembly **530**. A supply flow path **504** conveys supply fluid designated with arrow **505** and a return flow path **506** conveys return fluid designated with arrow **507**. As can be seen, the **Figure 6A** arrangement does not include
5 leak paths through which the high-pressure supply fluid **505** can invade the return flow path **506**. Thus, there is no need for high pressures seals.

In one embodiment, the motor **510** includes a rotor **512**, a stator **514**, and a rotating seal **516** that protects the coils **512** and stator **514** from drilling
10 fluid and cuttings. In one embodiment, the stator **514** is fixed on the outside of the drill string **502**. The coils of the rotor **512** and stator **514** are encapsulated in a material or housing that prevents damage from contact with wellbore fluids. Preferably, the motor **510** interiors are filled with a clean hydraulic fluid. In another embodiment not shown, the rotor is positioned within the flow
15 of the return fluid, thereby eliminating the rotating seal. In such an arrangement, the stator can be protected with a tube filled with clean hydraulic fluid for pressure compensation.

Referring now to **Figure 6B**, there is schematically illustrated one
20 arrangement wherein an electrically driven pump **550** includes a motor **570** that is at least partially formed integral with a drill string **552**. In a conventional manner, the motor **570** is coupled to a pump **590** via a shaft assembly **580**. A supply flow path **554** conveys supply fluid designated with arrow **556** and a return flow path **558** conveys return fluid designated with
25 arrow **560**. As can be seen, the **Figure 6B** arrangement does not include leak paths through which the high-pressure supply fluid **556** can invade the return flow path **558**. Thus, there is no need for high pressures seals.

It should be appreciated that an electrical drive provides a relatively
30 simple method for controlling the APD Device. For instance, varying the speed of the electrical motor will directly control the speed of the rotor in the APD device, and thus the pressure differential across the APD Device.

Further, in either of the **Figure 6A or 6B** arrangements, the pump **520** and **590** can be any suitable pump, and is preferably a multi-stage centrifugal-type pump. Moreover, positive displacement type pumps such a screw or gear type or moineau-type pumps may also be adequate for many applications.

5 For example, the pump configuration may be single stage or multi-stage and utilize radial flow, axial flow, or mixed flow. Additionally, as described earlier, a comminution device positioned downhole of the pumps **520** and **590** can be used to reduce the size of particles entrained in the return fluid.

10 It will be appreciated that many variations to the above-described embodiments are possible. For example, a clutch element can be added to the shaft assembly connecting the drive to the pump to selectively couple and uncouple the drive and pump. Further, in certain applications, it may be advantages to utilize a non-mechanical connection between the drive and the
15 pump. For instance, a magnetic clutch can be used to engage the drive and the pump. In such an arrangement, the supply fluid and drive and the return fluid and pump can remain separated. The speed/torque can be transferred by a magnetic connection that couples the drive and pump elements, which are separated by a tubular element (e.g., drill string). Additionally, while
20 certain elements have been discussed with respect to one or more particular embodiments, it should be understood that the present invention is not limited to any such particular combinations. For example, elements such as shaft assemblies, bypasses, comminution devices and annular seals discussed in the context of positive displacement drives can be readily used with electric
25 drive arrangements. Other embodiments within the scope of the present invention that are not shown include a centrifugal pump that is attached to the drill string. The pump can include a multi-stage impeller and can be driven by a hydraulic power unit, such as a motor. This motor may be operated by the drilling fluid or by any other suitable manner. Still another embodiment not
30 shown includes an APD Device that is fixed to the drill string, which is operated by the drill string rotation. In this embodiment, a number of impellers are attached to the drill string. The rotation of the drill string rotates the impeller that creates a differential pressure across the device.

Referring now to **Fig. 7**, there is shown a comminution device **600** for reducing the size of particles entrained in the returning drilling fluid. These particles can include rock and earth cut by the drill bit, debris from the wellbore, pieces of broken wellbore equipment, and other known items. For brevity, the term “crush” or “crushing” is broadly used to encompass any mechanical force, such as compression or shearing, that breaks up or otherwise disintegrates the entrained particles. Preferably, the comminution device **600**, which is positioned upstream of a selected wellbore device (e.g., the APD device **170** of **Fig. 1**), reduces the entrained particles to a size that will not jam, damage, or otherwise impair the operations of the selected wellbore device (e.g., APD device **170**).

In the **Fig. 7** embodiment, the device **600** includes a first stage **602** for reducing particles to a first selected size and a second stage **604** for reducing particles to a second selected size. The term selected size or predetermined size should be construed to cover ranges of selected or predetermined sizes as well. By way of a non-limiting illustration, the first stage **602** can reduce the diameter size of entrained particles to a range of approximately one hundred mm to forty-five mm and the second stage **604** can reduce the diameter size of entrained particles to a range of approximately fifty mm to ten mm. The ranges of particle reduction for the stages preferably overlap, but, this need not be the case. In one embodiment, each stage **602,604** is formed in a housing **606** wherein one or more cutting heads are disposed. Preferably, the comminution device **600** includes a first cutting head **608** and a second cutting head **610**.

The first stage **602** has an inlet **611** in fluid communication with the return fluid and a passage **612** that directs flow into the second stage **604**. The first cutting head **608** crushes entrained particles as they flow through a chamber **614** in the first stage **602**. Preferably, the chamber **614** is formed to promote circulation of the drilling fluid and minimize the settling of entrained

solids. Referring now to **Fig. 8**, for example, helix-like fins or ribs **616** formed on an inner wall **618** of the housing **606** “spin” or rotate the fluid such that the entrained particles circulate within the chamber **614**. Further, the inner wall **618** can include raised portions **620** or sidewalls that prevent particles from settling along the outer perimeter of the chamber **614**. Preferably, the housing **606** includes a first cutting surface **622** formed on a plane generally perpendicular to the longitudinal axis **A** of the device **600**. This cutting surface **622** can include a ramped or inclined section to accommodate the flow or return drilling fluid. Preferably, a second cutting surface **624** is formed on the inner wall **618** of the housing **606**. The first and second cutting surfaces **622,624** can include hardened surfaces adapted to withstand the forces and wear associated with the crushing or shearing of the entrained particles.

Referring now to **Figs. 7 and 9**, the first cutting head **608** is fixed to a drive shaft **626** and thereby suspended within the housing chamber **614**. The first cutting head **608** includes a first surface or face **628** that is generally perpendicular to the longitudinal axis **A** of the device **600** and a circumferential outer surface **630**. In one embodiment, the first face **628** and circumferential outer surface **630** are provided with raised cutting members **632** adapted to shear and/or crush entrained particles. The cutting members **632** include inclined planar portions **634**. Preferably, the cutting members **632** are configured such that the inclined planar portions **634** are aligned along multiple planes such that the entrained particles are subjected to different “angles of attack” for enhanced cutting. Thus, as the cutting head rotates, the first face cutting members **632** cooperate with the first cutting head **608** to reduce the size of particles flowing in a gap **635** therebetween. Likewise, the circumferential outer surface cutting members **632** cooperate with the second cutting surface **624** to reduce the size of particles traveling therebetween.

Referring now to **Fig. 7**, the second stage **604** has an inlet **636** in fluid communication with the first stage **602** and an exit **638** that directs flow to the selected wellbore device. Referring now to **Figs. 7** and **10**, preferably, the second cutting head **610** is generally disk-shaped and includes a plurality of longitudinal flow bores **640**. The size and number of the flow bores **640** will depend on the expected flow rate, size of entrained particles, and other factors known to one skilled in the art. The second stage cutting head **610** is fixed to the drive shaft **626** and thereby suspended in a chamber **642** formed in the housing **606**. Preferably, the return fluid can flow through both the flow bores **640** or a gap **644** provided between the second stage cutting head **610** and an inner surface **646** of the housing **606**. In other arrangements, return fluid flow can be directed to either the flow bores **640** or the gap **644**. The second stage **604** has a first cutting surface **648** formed on a plane generally parallel perpendicular to the longitudinal axis **A** of the device **600**. This cutting surface **648** can be inclined to accommodate the flow or return drilling fluid. A second cutting surface **650** is formed on the inner surface **646** of the housing **606**. The first and second cutting surface **648,650** can include hardened surfaces adapted to withstand the forces and wear associated with the crushing or shearing of the entrained particles.

20

The second cutting head **610** includes a first face **652** that is generally perpendicular to the longitudinal axis **A** of the device **600** and a circumferential outer surface **654**. In one embodiment, first face **652** and circumferential outer surface **654** are provided with raised cutting members **656** adapted to shear and/or crush entrained particles. The cutting members **656** are provided with inclined portions **658** having, preferably, multiple planar angles as described previously. Thus, as the second cutting head **610** rotates, the first face cutting members **656** cooperate with the first cutting surface **648** to reduce the size of particles traveling therebetween. Likewise, the circumferential outer surface cutting members **656** cooperate with the second cutting surface **650** to reduce the size of particles traveling therebetween. The second stage chamber **642** can also be formed to

30

promote circulation of the drilling fluid and minimize the settling of entrained solids; *e.g.*, members for “spinning” and preventing particles from settling along the outer perimeter of the chamber **642**.

5 The drive shaft **626** can be rotated by a suitable connection to the APD device **170** (**Fig. 1**), to a downhole power source such an electric or hydraulic motor (not shown), or to the drill string **121** (**Fig. 1**). Also, suitable axial and radial bearings **660** are provided to stabilize the cutting heads **608,610** during operation. Also, the comminution device **600** includes
10 crossover flow passages (not shown) for conveying supply fluid from a location uphole of the device **600** to a location downhole of the device **600**.

Referring now to **Figs. 7-10**, during operation, the return fluid **RF** enters the first stage chamber **614** via the housing inlet **603**. The first cutting
15 head **608** crushes the entrained particles to a selected size or range of sizes against the first cutting surface **622** with the cutting members **632** formed on the face **628**. Cutting members **632** formed on the outer circumferential surface of the first cutting head **608** can also crush the entrained particles flowing through the gap **635**. The drilling fluid and entrained particles flow
20 through the passage **612** to the chamber **642** of the second stage **604**. The second cutting head **610** further crushes the entrained particles to a smaller selected size or range of sizes. The entrained particles exit the chamber **642** after flowing through the second cutting head flow bores **640** and/or the gap **644** between the second cutting head **610** and housing **606**. Thereafter, the
25 return fluid and entrained cutting are directed to the downstream APD device **170** (**Fig. 1**).

Referring now to **Fig. 11**, there is shown another comminution device **700** for reducing the size of particles entrained in the returning drilling fluid. In
30 the **Fig. 11** embodiment, the device **700** includes a first stage **702** for reducing particles to a first selected size and a second stage **704** for reducing particles to a second selected size. Each stage **702,704** is formed in a

chamber **706** of a housing **708** wherein one or more cutting heads are disposed. In a preferred embodiment, the cutting heads include first and second frustoconical cutting rotors **710,712**. In one embodiment, the angles of the rotors **710, 712** and the inlet in the housing are chosen such that the entrained solids are continuously resized. For example, the gap between the cutters and the cutting surface is made progressively smaller along the flow path of the entrained particles.

The housing **708** has an inlet **714** in fluid communication with the return fluid and an exit **715** that directs return fluid **RF** to the selected wellbore device. Preferably, the housing **708** includes a first cutting surface **716** formed on an interior circumferential surface **718**. The first cutting surface **716** can include hardened surfaces adapted to withstand the forces and wear associated with the crushing or shearing of the entrained particles. The chamber **706** can also be formed to promote circulation of the drilling fluid and minimize the settling of entrained solids; *e.g.*, members for “spinning” and preventing particles from settling along the outer perimeter of the chamber **706**.

In a preferred embodiment, first and second frustoconical cutting rotors **710,712** are coupled in series to a shaft **720** and thereby suspended in the housing chamber **706**. The frustoconical cutting rotors **710,712** are configured to crush entrained particles as they flow through a chamber **706**. The cutting rotors **710,712** include an outer circumferential faces **722,724**, respectively, that are provided with cutting members **726** adapted to crush entrained particles. The cutting members **726** include lobes, grooves, teeth and other structures for crushing entrained particles. The cutting members **726** can be of the same configuration on each of the rotors **710,712** or of different configurations. Moreover, each rotor **710, 712** can include cutting members **726** of different configurations. Preferably, the cutting members **726** are set at multiple different angles or planes such that the multiple angles of attack are available during the crushing action. Preferably, the first and

second frustoconical cutting rotors **710,712** are arranged such that their smaller diameter ends are joined and their larger diameter ends are on opposing ends. Depending on the particular arrangement, the first and second frustoconical cutting rotors **710,712** can be of same or different
5 lengths, inclination (gradient or slope), or diameter. Moreover, a flow gap **734** between the cutting rotors **710,712** and the housing **708** is preferably sized to minimize the risk of plugging while allowing sufficient cutting action between the cutting rotors **710,712** and the cutting surface **716**.

10 The cutting rotors **710,712** are rotated by the drive shaft **720**. The drive shaft **720** can be rotated by a suitable connection to the APD device, to a downhole power source such an electric or hydraulic motor, or to the drill string. Also, suitable axial/thrust bearings **740** and radial bearings **738** are provided to stabilize the cutting rotors **710,712** during operation. The
15 comminution device **700** further includes crossover flow passages **736** for conveying supply fluid **SF** from a location uphole of the device **700** to a location downhole of the device **700**.

It should be appreciated that the present invention is not limited to any
20 particular number of rotors. In certain applications, a single cutting rotor may provide sufficient particle reduction. In other applications, three or more cutting rotors may be required to reduce entrained particles to a size that can pass through the APD device. Moreover, the rotors need not be frustoconical in shape. For example, they can be substantially cylindrical or include
25 arcuate surface. Factors to be considered with respect to the number of rotors and configuration of the cutting rotor and housing **708** include the size of the flow passages in the APD device, available torque for rotating the cutting rotors, the expected drilling fluid flow rate, and the rock content (*e.g.*, expected, size, density and nature of the particles).

30

During operation, the return fluid **RF** and entrained particles enters the chamber **706** via the inlet **714**. The first cutting rotor **710** cuts or crushes the

entrained particles to a selected size or range of sizes. The drilling fluid and entrained particles flow through the gap **732** between the first cutting rotor **710** and the housing **708** to the second cutting rotor **712**, which further crushes the entrained particles to a smaller selected size or range of sizes.

- 5 Thereafter, the return fluid and entrained cutting are directed to the downstream APD device (*e.g.*, positive displacement pump).

It should be understood that the present invention is not limited to multi-stage particle reduction. In certain applications, a single stage may provide sufficient particle reduction. In other applications, three or more stages may be required to reduce entrained particles to a size that can pass through the selected wellbore device. Factors to be considered with respect to the number of stages and configuration of the cutting head and housing include the size of the flow passages in the APD device, available torque for rotating the cutting heads, the expected drilling fluid flow rate, and the rock content (*e.g.*, expected, size, density and nature of the particles). Additionally, while the housing has been described as one element, the cutting heads can be housed in structurally separate housings. Moreover, the housing can be integral with the selected wellbore device. Further, it should be appreciated that the teachings of the present invention can be advantageously applied to any number of downhole applications wherein the size of particles in a return fluid are to be reduced in size *in situ* before returning to the surface. For instance, one or more independently operable comminution devices can be positioned along the drill string to adjust the density of the return fluid or to prevent the settling of larger particles along sections of the wellbore. In such instances, the particle reduction is controlled relative to selected parameter of the return fluid and not relative to the operating condition of a selected wellbore device.

30 Other embodiments, which are not shown, for reducing the size of particles include mills or devices wherein the axis of the rotational cutting action is generally parallel with the flow of the return fluid, which is usually along the longitudinal axis of the wellbore. In one embodiment, a housing can

include a frustoconical chamber for receiving a cylindrical cutter. The return fluid enters at the larger diameter of the chamber and exits at the smaller diameter. The cutter can be formed as a worm conveyer that, when rotated, draws entrained cuttings from the larger diameter section of the chamber to
5 the smaller diameter section of the chamber. The entrained particles are crushed as they flow through the gradually decreasing gap between the cutter and an inner wall defining the frustoconical chamber. In a related embodiment, the cylindrical cutter can be formed in a conical or frustoconical shape that generally conforms to the frustoconical shape of the chamber.
10 The gradients or angles of the chamber and cutter are set such that these spacing between the surfaces of the chamber and the cutter gradually reduces from an entry point to an exit point.

In another embodiment, cutting members such as teeth may be formed
15 on an inner surface of a cylindrical housing such as a stator. A rotor disposed in the stator crushed particles against the inner surface when rotated. The teeth have a profile and sufficient interstitial space for allowing solids to enter the inside of the stator. The height of the teeth gradually reduces in size so that the particles or solids cannot pass before they have been crushed
20 between the stator and the rotor. Holes provided in the stator can be provided to allow particles of a selected size to exit the stator.

In another embodiment, three conical or frustoconical rolls are oriented
is such a way so that the enveloped space between the rolls has a conical
25 shape. The diameter of the rolls becomes smaller with travel length of the solids allowing a continuous resizing of particles. One centrally disposed roll drives the other adjacent rolls. In another embodiment, a roller bit rotates on a plate. The roller bit includes wheel-like members that roll on the plate. During operation, roller bit rotation causes the wheel-like members to roll over
30 and crush particles, which exit the roller bit via holes.

In still other embodiments, the drive source or rotating action for crushing particles may be perpendicular to the flow of the return fluid. For

instance, two rollers may be positioned in a spaced-apart parallel orientation. In one embodiment, the two rollers are rotated in opposite directions such that solids and particles are pulled into the space between the rollers and crushed. In another embodiment, the rollers rotate in the same direction but at different rotational speeds. The particles, while being drawn between the rollers, are rotated, which provides flexible load points and enhances the crushing action. In yet another embodiment, one rotating roll works against a non-rotating plate to crush the particles. The rotating roll can include teeth having specified spacing. The distance between the roll and the plate and the space between the teeth determine the maximum size of the reduced particles.

In yet other embodiments, housing includes a rotating disk that has a plurality of radially oriented pistons. During disk rotation, centrifugal force urges the pistons move out of the disk. The rotating disk is disposed in a cavity or chamber such that during one part of the rotation, a wall of the chamber prevents the pistons from emerging from the disk and in another part of rotation, a gap is provided such that the piston can protrude from the disk. During operation, larger particles entering this gap are struck by the piston and crushed. Other particles are crushed between the disk and the wall of the chamber. In still other embodiments, a mortar can be used to crush solids.

In another embodiment, a hammer is disposed in a chamber and reciprocates along an axis transverse to the flow of drilling fluid through the chamber. A rod or other connecting member fixed to the hammer drives the hammer in an oscillating fashion against opposing walls defining the chamber. The entrained cuttings are crushed between the hammer and the walls. Biasing members such as springs coupled to the hammer can allow resonance operation.

In another embodiment, the drilling fluid is directed between a pair of opposing stamps. One or both of the stamps, which are plate-like members, can include flow holes through which entrained particles of a specified

diameter can exit. The stamps move together squeezing entrained particles therebetween.

5 In another embodiment, a screen is positioned upstream of the wellbore device. Only particles of a preselected size can pass through the screen. Once the screen is plugged with larger size particles, a bypass is opened to transport the larger cuttings past the wellbore device. Also, the particles can be collected in a tank or chamber and periodically conveyed to the surface. The particles can also be stored in the formation.

10

In still other embodiments, chemical, electrical, thermal, or wave energy can be used to disintegrate and reduce the size of entrained particles. For instance, an aggressive chemical can be injected into the return fluid. The chemical can either dissolve the particles or sufficiently soften the particles such that the particles disintegrate upon entering the wellbore device or perhaps by rubbing against the wellbore wall. The chemical can be supplied from a downhole reservoir that is periodically replenished by a fluid line to the surface or directly injected from such a fluid line. Embodiments utilizing electrical energy can include spark drilling, which can use electrical energy to evaporate entrained particles. The discharge point for the electrical energy can be integrated into a drill bit or positioned in the return fluid uphole of the drill bit. Other embodiments use a laser positioned proximate or uphole of the drill bit. The laser can produce a continuous or periodic beam that cuts the particles crossing the beam. In still other embodiments, the entrained particles are subjected to ultrasonic waves. The source for the ultrasonic source can be positioned proximate or uphole of the drill bit and reduce the size of particles entering an established wave field. It should be understood that the above-described embodiments can be combined with the described mechanical arrangements and methods for reducing the size of entrained particles. For instance, the larger size particles trapped by the screen can be collected in a chamber, as described previously, and then subjected to chemical, electrical, thermal, or wave energy. Thus, the reduction process is

30

made more efficient by focusing or limiting the discharge of energy to only the larger sized particles.

While the foregoing disclosure is directed to the preferred
5 embodiments of the invention, various modifications will be apparent to those
skilled in the art. For example, while a stator has been described as a cutting
surface, the rotor or other cutting member can crush entrained particles
against a wellbore wall, thereby eliminating the direction of return fluid into a
chamber. It is intended that all variations within the scope and spirit of the
10 appended claims be embraced by the foregoing disclosure.